Flexible Pipe Cap

Revision date:
19-03-2025

General Information

The Flexible Pipe Cap is designed to protect the interior of pipes from external elements, such as dirt, moisture, and debris, ensuring the pipe remains clean and uncontaminated during storage or transport. Its flexible material allows it to adapt to varying pipe sizes and conditions.

For application, the Flexible Pipe Cap is simply placed over the pipe end, where it securely clamps to the outer surface, providing a reliable seal without the need for additional tools.

Product specifications		
Product range* (pipe OD)	Ø50,8 – Ø1625,6 mm	(2” – 64”)
Application temperature	-40°C / +60°C	(-40°F / +140°F)
Venthole	On request	
UV-Resistance outdoor use	0,5 - 2 years	
Commodity / HS Code	39269097	

**Other sizes on request*

Features

- ✓ Fast and easy fitting and removal
- ✓ High resistance against tearing
- ✓ Suitable for a range of sizes

Flexible Pipe Cap	Flexible Pipe Cap

Material specifications

Material	: Low Density Polyethylene (LDPE)
Hardness	: 38° shore D
Elasticity at break	: 930 %
Tension at break	: 14 Mpa
Modulus of elasticity	: 65 Mpa
Material thickness	: approx. 2mm (0.08”)

Additional information

- Application time: Approximately 1-2 minutes per pipe end with a single person

Manufacturing & Sales Company
DHATEC B.V.
Dragonder 19
5554 GM Valkenswaard
The Netherlands

T: +31 (0)497 542 527
E: info@dhatec.nl
I: www.dhatec.nl

DHATEC®
Assets In Transit Deserve Optimal Care