

Datasheet Flexible Pipe Cap

Release date : 10-06-2013 Revision date : 26-05-2023

General information

The Flexible Pipe Cap closes the pipe against the elements. This protects the interior of the pipe.

Application

The Flexible Pipe Cap is placed over the pipe end and clamps itself to the outer pipe surface.

Features

- √ Fast and easy fitting and removal
- √ High resistance against tearing
- ✓ Suitable for a range of sizes

Material specifications

Material : Low Density Polyethylene (LDPE)

Hardness : 40° shore D
Elasticity at break : 1600 %
Tension at break : 21 Mpa
Modulus of elasticity : 60 Mpa

Material thickness : approx. 2mm (0.08")

Product range : 50.8 mm - 1.625.6 mm (2" - 64")

Product code : FC

Commodity / HS code : 39235090

Additional information

- Application temperature: -40°C / 60°C (-40°F / 140°F)
- UV-resistance: For outdoor use: 0,5-2 years
- Application time: 1 2 minutes per pipe end
- Available in a wide range of standard and non-standard sizes



Fig.1 Flexible Pipe Cap




Fig.2 Pipe with Flexible Pipe Cap

Manufacturing & Sales Company

DHATEC BV Dragonder 19 5554 GM Valkenswaard The Netherlands T: +31 (0)497 542 527

E: info@dhatec.nl

l: www.dhatec.nl www.sealforlife.com

