

## Datasheet PVC Plug with Bevel Protector

Release date : 23-05-2013  
Revision date : 05-06-2023

### General information

The PVC Plug is used in combination with the Dhatec Steel Bevel Protector to provide pipe end protection and pipe closure at the same time. The PVC Plug closed the pipe against the elements. This protects the internal pipe surface.

### Application

The PVC Pipe Cap is clamped inside the pipe with the steel Bevel Protector. The Clamping Clip will expand and the Bevel Protector forces itself strongly against the ID of the pipe.

### Features

- ✓ Bevel protection and pipe closure at the same time
- ✓ Suitable for long term pipe storage in all weather conditions
- ✓ Available in a wide range of standard and non-standard sizes
- ✓ Suitable for hook lifting

### Material specifications

Material : PVC  
Tensile strength warp : 2.500 N/5cm\*  
Tensile strength weft : 1.800 N/5cm\*  
Tear resistance warp and weft : 250 daN\*\*  
Weight : 570 gr/m<sup>2</sup> (1.3lbs / 10.8ft<sup>2</sup>)  
Application temperature : -30°C / 70°C (-22°F / 158°F)

Product range : 219,1mm – 3.048mm (8" – 120")  
Product code : PLVC

Commodity / HS code : PVC Plug: 39204390  
: Bevel Protector: 73269098

### Additional information

- UV-resistance: Suitable for long term outdoor use
- Application time: 1-2 minutes per pipe end  
\*acc. DIN 53 354 BS 3424 method 6A  
\*\*acc. DIN 53 356 BS 3424 method 7A



Fig. 1 PVC Plug with Bevel Protector



Fig. 2 PVC Plug with Bevel Protector in pipe

#### Manufacturing & Sales Company

DHATEC BV  
Dragonder 19  
5554 GM Valkenswaard  
The Netherlands

T: +31 (0)497 542 527  
E: info@dhatec.nl  
I: www.dhatec.nl  
www.sealforlife.com

 **SEALFORLIFE**  
Industries