

Datasheet Pipe Carrier Premium

Release date : 12-06-2013
 Revision date : 03-07-2023

General information

The Pipe Carrier Premium is suitable for storage and transport of small diameter pipes. It allows efficient and safe pipe handling and transport.

Application

The Base-Carrier is placed on the bottom. After placing the pipes on the Base-Carrier, the Mid-Carrier is positioned on top. The number of Carriers depends on the total weight of the pipes.



Fig.1 Pipe Carrier Premium

Types of Pipe Carrier Premium:

Type	Pipe diameter range [mm]	Max. load per recess [kg]	Max. load Base Carrier [kg]	Max. load Mid Carrier [kg]
6	Ø 114,3 – 194,2	1.436,0	8.616	8.616
5	Ø 177,8 – 235,0	2.233,7	11.169	11.169
4	Ø 219,1 – 296,3	2.750,0	11.000	11.000
3	Ø 273,1 – 398,3	3.429,7	10.289	10.289
2	Ø 355,6 – 508,0	5.050,1	10.100	10.100

Type	Pipe diameter range [inch]	Max. load per recess [lbs]	Max. load Base Carrier [lbs]	Max. load Mid Carrier [lbs]
6	Ø 4.50 – 7.65	3,165.8	18,995.0	18,995.0
5	Ø 7.00 – 9.25	4,924.5	24,623.4	24,623.4
4	Ø 8.63 – 11.67	6,062.7	24,250.8	24,250.8
3	Ø 10.75 – 15.68	7,561.2	22,683.4	22,683.4
2	Ø 14.00 – 20.00	11,133.6	22,266.7	22,266.7

Features

- ✓ Each carrier suitable for a range of pipe diameters
- ✓ Suitable for storage both for transport by train and truck
- ✓ Safe for pipe coating
- ✓ Reusable and safe for long term use in all weather conditions



Fig.2 Tubes on Pipe Carrier Premium

Manufacturing & Sales Company

DHATEC BV
 Dragonder 19
 5554 GM Valkenswaard
 The Netherlands

T: +31 (0)497 542 527
 E: info@dhatec.nl
 I: www.dhatec.nl
 www.sealforlife.com


SEALFORLIFE
 Industries

Material specifications:

- PE-compound, color black
 - Hardness: 92° shore A
 - Frictional resistance factor (F.r.): 0,3
 - F.r. with Anti-Skid rubber: 0,6
 - UV-stabilized
 - Application temperature: -45°C / 60°C (-49°F / 140°F)
 - Lifetime of approx. 15 years

Product range: 114,3 – 508,0 (4.5" - 20")

Product code: PCP

Commodity / HS code : 39269097

Additional information:

- Length of the carrier: 1.225mm (48.2")
- Width of the carrier: 115mm (4.53") Type 2: 130mm (5.12")
- Maximum load capacity as indicated in the instruction manual

Manufacturing & Sales Company

DHATEC BV
Dragonder 19
5554 GM Valkenswaard
The Netherlands

T: +31 (0)497 542 527
E: info@dhatec.nl
I: www.dhatec.nl
www.sealforlife.com

 **SEALFORLIFE**
Industries