

Datasheet Pipe Stop 50

Release date : 30-10-2013 Revision date : 11-04-2023

General information

Pipe Stop is a system consisting of a steel reinforced connectable rail system with matching blocks to support pipes during storage. Pipe Stop is adjustable for all diameters between 200mm and 2.575mm (7.87" – 102").

Application

The connectable bottom rails are placed on a flattened surface. The blocks can easily be positioned over the rails.

Features

- ✓ Safe pipe support
- ✓ Quick adjustability
- ✓ Suitable for coated pipe surfaces
- ✓ Durable, resistant against oil and moist
- ✓ Less material stress, improved roundness of the pipe

Material specifications:

Rails : Steel reinforced PE-Compound 4,031m

(13.2ft) / 46,5kg (102.5lbs)

Connector parts : Steel

PS50 Block type A : PE-Compound, 92°shore A; 5,43kg

(12lbs)

For pipe diameters: 200mm – 406mm

(7.87" - 16")

PS50 Block type B : PE-Compound, 92°shore A; 12,56kg

(27.7lbs)

For pipe diameters: 380mm - 670mm

(15" - 26.4")

PS50 Block type C : PE-Compound, 92°shore A; 8,19kg

(18.06lbs)

For pipe diameters: 660mm - 1.590mm

(26" - 62.6")

PS50 Block type D : PE-Compound, 92°shore A; 16,33kg

(36lbs)

For pipe diameters: 1.030mm – 2.575mm

(40.55" - 102")

Product range : 200,0mm – 2.575mm (7.87" – 102")

Product code : PS50

Commodity / HS code : 39269097



Fig.1 Pipe Stop



Fig.2 Pipe Stop parts: rails, blocks, connector, end stop, tool



Fig.3 Tubes on Pipe Stop

DHATECDragonder 19

5554 GM Valkenswaard The Netherlands

Contact Us

T: +31 497 542 527 E: info@dhatec.nl

I: dhatec.nl sealforlife.com





Additional information:

- Application temperature: -45°C / +60°C (-49°F / 140°F)
- For a temperature up to 40°C (104°F) a maximum load on 2 supporting lines: 50.000kg (110,231lbs) (Each pipe is supported on min. 4 positions)
- For a temperature up to 60°C (140°F) a maximum load on 2 supporting lines: 40.000kg (88,184lbs) (Each pipe is supported on min. 4 positions)
- Pipe Stop Measure-mate available for efficient installation

Dragonder 19 5554 GM Valkenswaard The Netherlands T: +31 497 542 527

E: info@dhatec.nl

I: dhatec.nl sealforlife.com

