

Pipe Closure Selection Table

Dhatec Solution:	Combined with Bevel Protector	Suitable for hook Lifting	IP Rating	Dustproof	Waterproof	Clamping force [N] / [lbf]	Impact force (no damage) [N] / [lbf]	Impact force (minimal damage) [J] / [ft. lbf]
Bevel protection:								
Bevel Protector	N/A	Yes	N/A	●●●●●	●●●●●	4.897 / 1.101	9.908 / 7.309	18.578 / 13.704
Plugs:								
PE Plug	Yes	Yes	IP-44	●●●●●	●●●●●	3.855 / 867	9.908 / 7.309	18.578 / 13.704
PVC Plug	Yes	Yes	IP-44	●●●●●	●●●●○	2.394 / 539	9.908 / 7.309	18.578 / 13.704
Sheets:								
PE Fiber Sheet	Yes	No	IP-40	●●●●●	●○○○○	2.453 / 552	9.908 / 7.309	18.578 / 13.704
Caps:								
Recessed Cap	No	Yes	IP-44	●●●●●	●●●●●	1.315 / 296	495 / 366	991 / 731
Flexible Cap	No	No	IP-44	●●●●●	●●●●●	530 / 120	495 / 366	991 / 731
Flexible Recessed Cap	No	Yes	IP-44	●●●●●	●●●●●	530 / 120	495 / 366	991 / 731

©Dhatec 2018 – TÜV NORD witnessed and approved – TÜV certificates on request

Dhatec specializes in developing and manufacturing solutions to ensure damage free pipes throughout the entire logistic supply chain. We advise manufacturers, coating plants, logistic companies, EPC contractors and end users how to achieve safe, efficient and damage free delivery of the pipes in any circumstance or climate.

Dhatec
 Dragonder 19
 NL-5554 GM Valkenswaard
 The Netherlands

Tel: + 31 497 542 527
www.dhatec.nl
info@dhatec.nl