

## **TÜV** NEDERLAND

P.O. Box 120 - 5680 AC Best - The Netherlands De Waal 21C - 5684 PH Best - The Netherlands 會 +31 (0)499 - 339500 - 昌 +31 (0)499 - 339539

## Test Results Dhatec Pipe Closure: Recessed Cap

Report nr: 2013-A-153 004 Revision 1

Released on: 9-JULY-2014







**Client** Dhatec BV

Elskensakker 8 5571 SK Bergeijk

Nederland

Tel: +31 (0) 497 542 527 Email: info@dhatec.nl Website: www.dhatec.nl

Project Test Results of Dhatec Recessed Cap, reference is

made to report 2013-A-153-000

Conclusion Resistance against cap removal:

An average force of 1.315 N is needed before the cap

releases from the pipe end.

Waterproofness and dustproofness:

Tests conform IEC 60529 result in classification IP44.

Impact test:

Beveled pipe with test object was subject to a 505 kg

drop weight for the impact test:

Drop Weight	No damage [J]	Damage [J]
Flat Plate	495	991

(Tests were executed at ±18°C and the impact test at ±20°C)

Date of execution

8-MAY-2014

Executed by:
M Verschoor f

M.Verschoor for TÜV Nederland QA B.V. L.van der Palen for Dhatec B.V.

Date of release

9-JULY-2014

Released by

Report number:

2013-A-153 004



© TÜV Nederland QA B.V.

All Rights Reserved.

No part of this report or any of its contents may be reproduced, copied, modified or adapted, without the prior written consent of the TÜV Nederland QA B.V. Commercial use and distribution of the contents of this report is not allowed without express and prior written consent of TÜV Nederland QA B.V.

The General Terms and Conditions of TÜV Nederland QA BV are applicable to this document. The general terms and conditions can be downloaded through our website www.tuv.nl.