

 TÜV NEDERLAND

 P.O. Box 120 - 5680 AC
 Best - The Netherlands

 De Waal 21C - 5684 PH
 Best - The Netherlands

 ☎ +31 (0)499 - 339500 - 昌 +31 (0)499 - 339539

### Test Results of Dhatec Bevel Protector in combination with Plastic Plug

Report nr: 2013-A-153 006 Revision 1

Released on: 9-JULY-2014



# Member of TÜV NORD Group

Report 2013-A-153 006 REV 1

Issued by TÜV NEDERLAND QA B.V.

Page 1 of 5



Client	Dhatec BV Elskensakker 8 5571 SK Bergeijk Nederland Tel: +31 (0) 497 542 527 Email: <u>info@dhatec.nl</u> Website: <u>www.dhatec.nl</u>		
Project	Test Results of Dhatec Bevel Protector in combination with Plastic Plug, reference is made to report 2013-A- 153-000		
Conclusion	Resistance against removal: An average force of 3.855 N is needed before the bevel protector and plastic plug release from the pipe end. Waterproofness and dustproofness: Tests conform IEC 60529 result in classification IP44. Impact test: Beveled pipe with test object was subject to a 505 kg drop weight for the impact test:		
	Flat Plate	9.908	18.578
	Half Plate	7.431	12.385
	Ø 52 mm pipe	991	1.486
	(Tests were execute	ed at ±18°C and the im	pact test at ±20°0
Date of execution	Executed by:		

## Date of execution 8-MAY-2014

Date of release 9-JULY-2014

Released by

**Report number:** 2013-A-153 006

#### Executed by:

M.Verschoor for TÜV Nederland QA B.V. L.van der Palen for Dhatec B.V.

Member of TÜV NORD Group Author	Review
Name	Name

#### © TÜV Nederland QA B.V.

All Rights Reserved.

No part of this report or any of its contents may be reproduced, copied, modified or adapted, without the prior written consent of the TÜV Nederland QA B.V. Commercial use and distribution of the contents of this report is not allowed without express and prior written consent of TÜV Nederland QA B.V. The General Terms and Conditions of TÜV Nederland QA BV are applicable to this document. The general terms and conditions can be downloaded through our website www.tuv.nl.